Tel.: +86 20 39388220 Fax: +86 20 31072811 Web: <u>http://www.rhaudiopa.com/</u> Email: <u>info@rh-audio.net</u>

## 2.0 Powered Wall Mounting WiFi Speaker RH609WF

## Features of 2.0 Powered Wall Mounting WiFi Speaker RH609WF

Active master loudspeaker "L"

- % Built-in 2-channel digital stereo amplifier (Class D) 2\*30W.
- \* Built-in WiFi receiver.
- % 2-way speaker system woofer 5" + tweeter 1" drivers.
- % With one 6.35mm MIC jack input.
- % "L&R" of unbalanced inputs via RCA connectors.
- ※ 100V signal input via RCA connector available.
- ※ BASS and TREBLE tone controllers.
- % Individual volume control for line, WiFi, microphone and 100V signal input.

Passive slave loudspeaker "R"

- <sup>™</sup> Rated power 30W.
- % 2-way speaker drivers woofer 5" + tweeter 1".
- \* Phoenix connector ready to be connected to the main loudspeaker "L".

## **Descriptions of 2.0 Powered Wall Mounting WiFi Speaker RH609WF**

The <u>RH-AUDIO</u> 2.0 Powered Wall Mounting WiFi Speaker RH609WF is ompatible for Android, iOS with APP control WiFi audio for independent control of music content by multiple users via APP Streaming music directly from phone.Featured RJ45 network port for wired connectivity is a backup for the point where the WiFi signal is weaker and one LINE input for local audio source.

The system uses a master/slave speaker configuration, in the master speaker there is a two channel Class D stereo power amplifier with speaker outlets to power the Slave speaker.

Also includes one 100V input is available to receive the remote amplified signal then converted to low line signal internally, and one 6.35mm socket is ready for connecting the local wired microphone.

These speakers utilize coaxial ceiling speaker system of 5" PP cone woofer and 1" titanium dome tweeter to allow for superior sound and clear intelligibility in a variety of environments. And supplied with adjustable wall mounting brackets, and colors are optional in black and white, ideal for AV applications such as meeting rooms, multi-media rooms for small presentations.



Tel.: +86 20 39388220

Web: <u>http://www.rhaudiopa.com/</u> Email: info@rh-audio.net

Fax: +86 20 31072811

Specifications of 2.0 Powered Wall Mounting WiFi Speaker RH609WF

Model	RH609WF
Rated Power	2*30W@8 Ω
Amplifier Channel	2 Channel
Amplifier Type	Digital Class D
Frequency Response	80Hz-18KHz(±3dB)
THD	<0.05% at 1kHz,1/3 rated power
S/N	>70 dB
Speaker Unit	Woofer 5"*1 + tweeter 1"*1
Power Consumption	50W
Installation	Wall mounting
Material	ABS enclosure, metal clamps
Power Supply	AC100V-240V/50Hz/60Hz
Fuse	T1.5A*1
Dimension	170*185*250mm
Net Weight	4.80kg (1+1)

