Tel.: +86 20 39388220 Web: http://www.rhaudiopa.com/

Fax: +86 20 31072811 Email: <u>info@rh-audio.net</u>

6inch Dual-cone Dynamic Ceiling Speaker RH-T13



- % Full-range 6", 6 W dual-cone dynamic speaker.
- * 100 V line transformer features two taps for 3 W and 6 W outputs.
- ** This technique of line input 100V reduces signal losses on a longer distance and allows easy parallel connection of multiple loudspeakers.
- * Frame-mounted spring-loaded clamps provide secure, low-noise connections and easy installation.
- * Attractive color ABS resin finish with white grille suits any decor.

Description

This <u>RH-AUDIO</u> 6" Dual Cone Ceiling Speaker RH-T13 has compact size design and attractive appearance with economical cost.

Widely used in evacuation, public address and background music applications. It is ideal for areas such shopping centres, hotels and large indoor public areas or indeed any area where background music and paging is common and therefore excellent audio reproduction is critical.

Spray-painted steel protection grille comes against rust and oxidization.

Compact enclosure made of high-quality ABS material finished in white color ensures its long life service.

It enjoys 6W dual cone dynamic loudspeaker drive providing high performance with a wider frequency response range and improved speech intelligibility.

Built-in multi-tapped transformer for 100/70V constant voltage connection with 3W and 6W available. Its frame-mounted spring-loaded clamps provide secure, low-noise connections and easy installation.



Tel.: +86 20 39388220 Web: <u>http://www.rhaudiopa.com/</u>


Fax: +86 20 31072811 Email: <u>info@rh-audio.net</u>


Product Details:





Tips of Installation:






Retract the 2 Snap Clamps on the speaker into their open position. Then push the speaker up through the ceiling opening.

When Clamp Arms press against the ceiling, the Snap Clamps will rotate and clamp down closed to the ceiling surface.

Specifications of <u>6" Dual Cone Ceiling Speaker RH-T13</u>:





Tel.: +86 20 39388220 Web: <u>http://www.rhaudiopa.com/</u>

Model	RH-T13
Rated Power	3W/6W
Line Voltage	100V
Frequency Response	110Hz-15KHz
Sensitivity(1w,1 n)	90±3 dB
Hole for mount ing	ф 170mm
Dimension	ф 188*76mm
Finished	Baffle & Enclosure: ABS resin; Grille & Mounting Hardware Steel alloy.
Mounting Meth od	Frame-mounted spring-loaded clamps
Speaker Unit	6" dual-cone,paper
Weight	0.75Kg