

Tel.: +86 20 39388220
Fax: +86 20 31072811

Web: <http://www.rhaudiopa.com/>
Email: info@rh-audio.net

IP Speakers RH6030 & RH6060



- ※ With Power Saving Mode.
- ※ Built-in D type digital amplifier.
- ※ Two way system with separate woofer and tweeter.
- ※ All metal extruded aluminum alloy enclosure with cast aluminium top and bottom plates are fully dust free and waterproof IP65 rated, suitable for in/outdoor use.
- ※ Support protocols of UDP,TCP/IP,IGMP.
- ※ Standard Rj45 network port.
- ※ Easy and secure installation through the supplied strong metal mounting brackets.
- ※ Are suitable varied applications such as stations,gardens, swimming pools,stadiums,and tennis courts,etc.

Description

The [RH-AUDIO](#) Full-weather IP Speaker Column Series which produce good clear sound and acoustical clarity for background music and paging,are suitable for indoor and outdoor applications such as stations,gardens, swimming pools,stadiums,and tennis courts,etc.

Even in extreme weather conditions, the all metal extruded aluminum alloy enclosure with cast aluminium top and bottom plates are fully dust and weatherproof, IP65 rated.

Easy and secure wall mount installation in outdoor area through the supplied strong metal mounting brackets.



Guangzhou Xinghongde Electronics Technology Co.,Ltd.

Tel.: +86 20 39388220

Web: <http://www.rhaudiopa.com/>

Fax: +86 20 31072811

Email: info@rh-audio.net

Specifications of [Full-weather IP Speaker Column Series](#)

Model	RH6030	RH6060
Rated Power	30W	60W
Network Port	Standard RJ45×1	Standard RJ45×1
Protocols	TCP/IP,UPP,IGMP	TCP/IP,UPP,IGMP
Audio Format	MP3/MP2	MP3/MP2
Sampling Rate	8K~48KHz	8K~48KHz
Network Rate	10Mbps	10Mbps
Audio Quality	16 bits of stereo, CD timbre	16 bits of stereo, CD timbre
Output Frequency	80Hz~16KHz	80Hz~16KHz
THD	≤%1	≤%1
S/D	>70dB	>70dB
Rated Power	30W	60W
Speaker Unit	6.5inch woofer x2+1.5inch tweeter x1	6.5inch woofer x2+1.5inch tweeter x1
Working Temperature	-20°C~+60°C	-20°C~+60°C
Working Humidity	10%~90%	10%~90%
Consumption	≤90W	≤90W
Power Supply	AC 110V-240V/50Hz/60Hz	AC 110V-240V/50Hz/60Hz
Protection	AC FUSE*T1.6A	AC FUSE*T1.6A
Power Cord	3*0.75mm*0.5M	3*0.75mm*0.5M
Product Size	320(H)×190(W)×175(D)mm	320(H)×190(W)×175(D)mm



Guangzhou Xinghongde Electronics Technology Co.,Ltd.