

Tel.: +86 20 39388220
Fax: +86 20 31072811

Web: <http://www.rhaudiopa.com/>
Email: info@rh-audio.net

Desktop Paging Microphone RH300MC



The [RH-AUDIO](#) Desktop Paging Microphone RH300MC is designed with high quality condenser, matching with controlled circuit.

This [desktop microphone](#) has ultra-cardioid polar pattern and high sensibility, and also match with the circuit which can remove the noise when turn the on-off switch, is a popular choice for use in shops, convention halls, stations and schools etc.

Further more the dynamic microphone RH300MC enjoys following features:

Compact desktop paging microphone with gooseneck positioning flexibility for sound reinforcement applications, ideal for PA system.

Exudes excellent speech and intelligibility.

Cuts through noisy backgrounds of live miking situations and large gatherings.

Effective control of feedback, reduced ambient handling noise, and low sensitivity to breath and popping sounds.

Features a wire-mesh wind filter.

Table stand with on/off switch.

Built-in 2-tone chime unit.

- ※ Compact desktop paging microphone with gooseneck positioning flexibility for sound reinforcement applications, ideal for PA system or any podium.
- ※ Exudes excellent speech and intelligibility.
- ※ Cuts through noisy backgrounds of live miking situations and large gatherings.
- ※ Effective control of feedback, reduced ambient handling noise, and low sensitivity to breath



Guangzhou Xinghongde Electronics Technology Co., Ltd.

Tel.: +86 20 39388220

Web: <http://www.rhaudiopa.com/>

Fax: +86 20 31072811

Email: info@rh-audio.net

and popping sounds.

※ Features a wire-mesh wind filter.

※ Table stand with on/off switch.

※ 2 tones prior to speaking.

The specifications of [wireless desktop microphone](#):

Model	RH300MC
Capsule Type	Condenser
Frequency Response	40Hz-16KHz
Polar Pattern	Super Cardioid
Output Impedance(Ohm)	200
Sensitivity (± 2 dB)	- 38dB
Power Supply	DC9V / AC220V adapter
Length (mm)	420
Net Weight	0.67kg
Sound Pick-up Distance	40cm
Battery Working Time (hour)	18
Base Dimension(WxDxH)mm	126*150*39mm
Output/Indicator	Unbalance, Base indicator

