

Tel.: +86 20 39388220  
Fax: +86 20 31072811

Web: <http://www.rhaudiopa.com/>  
Email: [info@rh-audio.net](mailto:info@rh-audio.net)

## IP Based Remote Microphone RH8310



**RH-AUDIO** The IP Based Remote Microphone RH8310 is the core control equipment for IP based public address system, is an all-in-one network microphone console features two-way communication via a high-quality 41cm-length gooseneck microphone and an integrated full-range 8Ω/5W speaker, also with SD/USB/LINE-IN ports, plus its own built-in audio management server.

[microphone ip](#) allow users to play local audio materials directly to the other IP terminals in a complete public-address system.

That allow users to have several paging modes including individual-zone paging, combined-zones paging and all-zones paging, even more its a listen-in function that allows users to monitor audio in a zone/zones selected.

All the operations are made through its user-friendly interface (a colorful 7 inch TFT LCD touch screen).

Very easy for deployment, anywhere has internet then could access in, normally install in control center or leaders office, quite suitable for organizations with complex inter-building distribution and scheduling needs such as government agencies, schools, factories, commercial buildings, residential areas and hospitals etc.

Main Core Features of [ip microphone](#) included are:

- ※ Support for hands-free and non hands-free dual-mode phone: external gooseneck microphone, built-in speakers, support for hands-free calls.
- ※ With microphone interface, can connect to professional microphone, to a hands-free calls.
- ※ With 7 inch color LCD touch screen, could directly do IP address configuration, and check the



Guangzhou Xinghongde Electronics Technology Co., Ltd.

Tel.: +86 20 39388220

Web: <http://www.rhaudiopa.com/>

Fax: +86 20 31072811

Email: [info@rh-audio.net](mailto:info@rh-audio.net)

terminal status.

- ※ Support two way intercom,between two way intercom terminals.
- ※ Has many one key calling button,easy call different zone.
- ※ One key for help,intercom,easy connection.
- ※ Monitor function,for environment monitor which sounds collected from other terminals.
- ※ Support static state IP and DHCP two modes,across different network segment, routing,easy configuration.
- ※ 3.5mm standard audio port,connect with professional microphone, extend non hands-free calls,for secret communication.
- ※ Support 1 line local output,cold connect to amplifier.
- ※ Support U disk on demand play,contents in U disk,could on demand to other terminals.
  
- ※ High-quality 41cm-length gooseneck microphone.
- ※ Built-in full-range 8Ω/5W speaker.
- ※ Support paging modes: individual/combined/all zone.
- ※ Support two-way intercom between two-way IP terminals.
- ※ Colorful 7 inch color LCD touch screen.
- ※ 1 internet connection(LAN): RJ45.
- ※ Built-in MP3 player with SD & USB ports on the rear.
- ※ 1 U-KEY port for forauthorize operation.
- ※ 1 line local input for connecting external audio source.
- ※ 1 line local output for connecting addtional amplifier.
- ※ 1 MIC. Input for professional microphone, for non hands-freecalls.
- ※ 1 DC12V power inlet.



Guangzhou Xinghongde Electronics Technology Co.,Ltd.