Tel.: +86 20 39388220 Web: http://www.rhaudiopa.com/

Fax: +86 20 31072811 Email: <u>info@rh-audio.net</u>

Two Way Sound Reinforcement Speaker



The <u>RH-AUDIO</u> Two Way Sound Reinforcement Speaker RH-MS65 is designed with woofer and tweeter, the woofer is constructed from polypropylene and has a rubber surround, the directional tweeter has a ferrofluid cooled silk dome.

This wall mounting speaker utilizes ABS enclosure and a sturdy metal grille, suitable for free standing or wall mounting via adjustable fixing bracket, its trapezoidal design allows for the enclosures to be mounted neatly into corners, making them ideal for most applications of high-voltage audio distribution systems.

Available in white or black finish, and U shaped stainless and rotatable mounting bracket is supplied.

The characteristics of 2 way loudspeaker:

- * 2-way wall mount speaker system.
- X Speaker drivers: Woofer 6" and tweeter 1" speaker unit.
- ** Built-in 100V transformer (this technique of line input 100V reduces signal losses on a longer distance and allows easy parallel connection of multiple loudspeakers).
- * High quality ABS enclosure, metal grille and bracket, black and white available.
- * Fast installation by U shaped stainless and rotatable mounting bracket could be adjusted at request.



Tel.: +86 20 39388220 Web: http://www.rhaudiopa.com/

The specifications of <u>2 way outdoor speakers</u>:

Model	RH-MS65
Rated Power (W)	40W
Audio Input	100V
Freq.Resp.(HZ)	80Hz-15KHz
Sensitivity (1w,1n)	91±3 dB
Dimensions (mm)	185*280*130mm (W*H*D)
Material	ABS enclosure &metalgrille
Net Weight	2.8kg
Speaker Unit	6"*1 woofer + 1"*1 tweeter