Tel.: +86 20 39388220 Web: http://www.rhaudiopa.com/

Fax: +86 20 31072811 Email: <u>info@rh-audio.net</u>

Two Way Voice Alarm Speakers



The <u>RU-AUDIO</u> Two Way Voice Alarm Speaker RH-MS15 Series offers three sizes of options with rated power 20W,30W,40W separately. These 100 volt distributed speakers use two-way sound system by adopting polypropylene woofer driver and silk dome tweeter.

Built-in step-down transformers to simplify impedance calculations and to minimize power loss over the speaker cables, are most appropriate for high-voltage audio distribution systems.

The trapezoidal design allows for the enclosures to be mounted neatly into corners with U shaped stainless and rotatable mounting bracket is supplied.

A sophisticated version with wattage tappings selectable by an integral rotary switch on rear for selections of 70 volt,100 volt and 8 Ohm.

The characteristics of speaker alarm:

- * 2-way wall mount speaker.
- * Three speaker sizes are available with separate woofer size 4", 5" and 6".
- * Black and white color are available.
- ** Built-in 100V transformer (this technique of line input 100V reduces signal losses on a longer distance and allows easy parallel connection of multiple loudspeakers).
- * Also 8 Ohm input is available without transformer.
- * ABS enclosure, metal grille, metal bracket.
- * Fast installation by U shaped stainless and rotatable mounting bracket could be adjusted at request.

The specifications of voice fire alarm:

Model	RH-MS15/4	RH-MS15/5	RH-MS15/6
Rated Power (W)	20W	30W	40W
Line Voltage (V)	100V	100V	100V



Tel.: +86 20 39388220 Web: <u>http://www.rhaudiopa.com/</u>

Freq.Resp.(HZ)	100Hz-20KHz	100Hz-20KHz	70Hz-20KHz
Sensitivity (1w,1n)	89±3 dB	87±3 dB	88±3 dB
Dimensions (mm)	215*170*150 mm	242*182*162mm	284*215*190mm
Material	ABS enclosure, metal grille, metal bracket; Black and White availa ble		
Net Weight	2.2kg	2.5kg	3.5kg
Speaker Unit	4"*1+1"*1	5"*1+1"*1	6"*1+1"*1